

**Atty Docket No.: IDF 1767
(4000-07000)**

Patent

LISTING OF THE CLAIMS:

1. (Original) A method for notifying a user device coupled to an integrated services hub that communication has been terminated with a remote device comprising:
receiving a disconnect signal from the remote device into the integrated services hub;
determining the status of the user device; and
when the user device is off-hook, relaying a call termination notification signal to the user device from the integrated services hub via a user device interface coupled to the user device.
2. (Original) The method of claim 1 wherein the call termination notification signal comprises temporarily placing the user device interface in a disabled state.
3. (Original) The method of claim 2 wherein the disconnect signal is received from the remote device by a network interface within the integrated services hub.
4. (Original) The method of claim 3 wherein the network interface is a WAN interface.
5. (Original) The method of claim 3 wherein the network interface sends the disconnect signal to a CPU within the integrated services hub.

**Atty Docket No.: IDF 1767
(4000-07000)**

Patent

6. (Original) The method of claim 5 wherein the CPU determines the user device to which the disconnect signal pertains.

7. (Original) The method of claim 6 wherein the call termination notification signal is sent from the CPU to the user device interface coupled to the user device.

8. (Original) The method of claim 7 wherein the user device interface is a SLIC.

9. (Original) The method of claim 8 wherein the call termination notification signal sent to the SLIC indicates to the user device that the user device should enter an on-hook status.

10. (Original) The method of claim 9 wherein the CPU places the SLIC in a standby state upon the user device entering an on-hook status.

11. (Original) The method of claim 10 further comprising:

detecting the status of the user device by the CPU after sending the call termination notification signal to the SLIC; and

when the user device is in an off-hook status, sending another call termination notification signal to the SLIC.

**Atty Docket No.: IDF 1767
(4000-07000)**

Patent

12. (Original) A method for defining the status of a user device upon termination of communication with a remote device comprising:

receiving a disconnect signal from the remote device;

determining the status of the user device via a CPU monitoring a user device

interface coupled to the user device;

when the user device is off-hook, sending a call termination notification signal to the user device interface;

interpreting the call termination notification signal by the user device as notification for the user device to enter an on-hook status; and

placing the user device interface in a standby state upon the placement of the user device in an on-hook status.

13. (Original) The method of claim 12 wherein the user device interface is a SLIC.

**Atty Docket No.: IDF 1767
(4000-07000)**

Patent

14. (Original) An apparatus for notifying a user device coupled thereto that communication has been terminated with a remote device comprising:

a network interface configured for receiving a disconnect signal from the remote device into the apparatus;

a CPU coupled to the network interface and configured for determining the status of the user device; and

a user device interface coupled to the user device and the CPU and configured for relaying a call termination notification signal from the CPU to the user device when the user device is off-hook.

15. (Original) The apparatus of claim 14 wherein the apparatus is an integrated services hub.

16. (Original) The apparatus of claim 15 wherein the network interface is a WAN interface.

17. (Original) The apparatus of claim 16 wherein the user device interface is a SLIC.

18. (Original) The apparatus of claim 17 further comprising a SLAC coupled to the SLIC and the CPU, the SLAC having an internal register for indicating the state of the SLIC, the internal register being accessible by the CPU.